CK2810 KIOTI Compact Tractor













14001 OHS

Standard Equipment

- Rear Remote Hydraulic Valve
- Rear PT0
- 4WD
- Parking Brake
- Battery
- Horn
- Signal Lamp
- PTO Cover
- ROPS
 Cup Holder
- Precleaner



New Compact design

Compact but more Powerful CK2810 comes with new streamlined hood design, which improves visibility andservice ability of the operator. A vertical opening hood allows for easy access to the air filter, fluid service, use box and electrical components for inspection.



Powerful Environmentally Friendly Engine
The Powerful Environmentally Friendly
28hp 'Green' Engine will offer operator
quietest, smoothest but most powerful
working condition.



Operator Station

All control levers are easy to reach and allow the operator to work in comfort.

The instrument panel is easily visible and the operator can monitor all operations at a glance.

Specifications

MODEL		082010
ENGINE		
Make		Daedong
Model		3A139LWB
Type		3Cyl., In-Line Vertical, Water-Cooled
Engine Gross Power	HP(kw)	28(20.8)
No, of Cylinders		3
Displacement	CC	1,393
Rated Revolution	rpm	2,600
Fuel Tank Capacity	Q	25
Engine Oil	Q	5.8
PTO		
Rated PTO Power	HP(kw)	22.9(17)
Rear PTO Type	/ II ((CT)	Transmission
Rear PTO Speed	rpm	540, 750
DRIVE TRAIN	ipiii	340,730
Transmission		Manual
		6F x 2R
Speeds Differential Leak		
Differential Lock		Rear Standard
Steering		Power Steering
Main Clutch Type		Dry Single
Brake		Wet Disc Type
Front Wheel Drive System		Mechanical
HYDRAULIC SYSTEM		
3 Point Lift Control Type		Position
Implement Pump	lpm	26
Power Steering Pump	lpm	16.9
Total Hydraulic Flow	lpm	42.9
3 Point Hitch Type		Category I
Lift Capacity at Lift Point	kg.f	739
Drawbar Type		Bar
No. of Standard Remote Valves (Front/Rear)		(-/1)
TIRE SIZE		
AG Tire		-
Front		7-12
Rear		11.2-16
TRAVELING SPEEDS		1116
Forward	km/h	0~17.15
Reverse	km/h	0~12.01
OTHERS	1011/11	0 12.01
Tilt Steering		
One-Touch Hood Type		Std
Panel Type		Electric
DIMENSIONS		0.400
Overall Length (W/O Front Weight and 3Pt Hitch)	mm	2,432
Overall Width (Minimum Tread)	mm	1,250
Tread Width - Front	mm	989
Tread Width - Rear	mm	950
Overall Height (ROPS)	mm	2,150
Wheel Base	mm	1,520
Ground Clearance	mm	330
Weight (with ROPS)	kg.f	1,025

^{*}NOTE : Specifications and design are subject to change without notice



Lasso – Latacunga - Babahoyo Panamericana Sur KM 44 (matriz) +(593) 3 2700 203

+(593) 99 702 8131 www.tractorkioti.com

www.agroscopio.com