

Fits DK10 Series Models. (DK4510, DK4510HS, DK5010, DK5010HS, DK5510, DK5510HS) The KIOTI KL5510 front end loader is specifically designed for the DK10 Series tractors, providing efficient performance with single lever joystick control. The KIOTI loader, with a built-in parking stand, is designed to be quickly and easily attached and detached. KL Series loaders utilize the tractor's hydraulic system, feature single-lever control with float and come with a bucket level indicator. *Specifications may vary with tractor model, front axle configurations, tire size option and type of attachment and are subject to change without notification.





Specifications

Maximum Lift Height to pivot pin	109 in. (2,768 mm)
Clearance w/ Attachment Level	96.4 in. (2,449 mm)
Clearance w/ Attachment Dumped	81.7 in. (2,075 mm)
Reach at Maximum Height	18.1 in. (460 mm)
Maximum Dump Angle	58°
Reach w/ Attachment on Ground	70.9 in. (1,800 mm)
Maximum Rollback Angle	38.9°
Digging Depth Below Grade	9.1 in. (231 mm)
Overall Height in Carry Position	57.7 in. (1,465 mm)
Depth of Attachment (to back of inner shell)	18.4 in. (467 mm)
Height of Attachment	22 in. (560 mm)
Length of Attachment (to pivot pin)	26 in. (660 mm)
Lift Capacity to Full Height at Pivot Pins	2,660 lbs. (1,207 kg)
Breakout Force at Pivot Pin	3,900 lbs. (1,769 kg)
Bucket Size	66 in. / 72 in.
Weight (with Bucket)	1,452 lbs. (180 kg)