



GREEN-RITE

Overseeders & aerators
25-70 HP (19-52 KW)
540 rpm - Cat. 1

- Special 2.8" spacing on rotor for aerating with 3 knives per flange; 4 knives on 82"
- 2" to 3" suggested working depth with aerator rotor, 7 1/4" working depth with tiller rotor; 8 3/4" on 82"
- Seed covering/dethatching adjustable tickler tines
- High precision metering seed cups made from a nylon/fiberglass composite
- Parking stand
- Ground drive system for seed hopper
- Large capacity seed hopper with agitator
- Heavy duty shielded PTO shaft with slip clutch safety (1 3/8" ASAE cat. 3 for models 250, 258 & 266, cat. 6 for model 282)
- Corrugated depth control roller made with low weight nylon/fiberglass roller rings
- Double sided, extra thin profile razor blades reduce impact when aerating over existing turf (available on request)





• **TECHNICAL FEATURES**

Model	HP	Hitch	Working width	Overall width	Weight lbs	Ship lbs	Capacity cu. ft.	# Seed cups	# Flanges	# Blades	Chain sprockets	Rotor rpm	Maximum working depth	Driveline 1 3/8"
GRT-250	25-45	Cat. 1	50"	57"	910	1,160	4.6	7	15	43	11-14	231	7 1/4"	ASAE cat. 3 slip clutch
GRT-258	30-45	Cat. 1	58"	66"	998	1,245	5.3	8	18	52	11-14	231	7 1/4"	ASAE cat. 3 slip clutch
GRT-266	32-45	Cat. 1	66"	74"	1,170	1,390	6	9	21	61	11-14	231	7 1/4"	ASAE cat. 3 slip clutch
GRT-282	40-70	Cat. 1	82"	89"	1,500	1,760	7.6	11	26	104	12-14	221	8 3/4"	ASAE cat. 6 slip clutch

WARNING: When using a quick hitch on a PTO driven implement, always ensure there is proper overlap prior to use. If there is not the minimum 6" overlap, do not use. Contact your dealer to purchase a longer driveline.