

# AIRBLAST SPRAYER WITH ADJUSTABLE CANNON HEAD

FRAME IN HOT-DIP GALVANIZED STEEL SECTIONS,  
POLYETHYLENE TANK WITH TOTAL EMPTYING AND FOLDING LID.

**Circuit washing tank.** Fresh water tank, external level, suction filter with valve, tank mixer, drain valve, remote controller.  
Hot galvanized fan casing, nozzle holder rods in stainless steel. Centrifugal impeller.  
2-speed gearbox with disengagement and CLUTCH, with 2 hydraulic movements (rotation at 360° and inclination at 90°), manual nut rotation with fifth wheel, single nozzles with membrane anti drip and ceramic nozzles of 1.5-1.2 mm.

**Delivered without hydraulic hoses.**



## ATP Adjustable Cannon Head

200 - 300 - 400 - 600 L

CODE	Tank capacity	Pump	Pressure Reg.	L/min	BAR	Absorbed power	Fan Ø	Nozzles	Spray Range A+B	Dimensions cm	Weight
<b>MOUNTED AIRBLAST SPRAYERS WITH ADJUSTABLE CANNON</b>											
M2302CO9	200 L	AR 503	GR 30	55,0	40,0	22,0	400 SINGLE	7+3	25+18	80x120x150	215
M2303CO9	300 L	AR 503	GR 30	55,0	40,0	22,0	400 SINGLE	7+3	25+18	95x150x160	255
M2304CO6	400 L	AR 503	RM 40	55,0	40,0	22,0	400 SINGLE	7+3	25+18	95x150x160	261
M2304CO7	400 L	AR 813	RM 40	80,0	50,0	30,0	400 SINGLE	7+3	25+18	95x150x160	270
M2304CO3	600 L	AR 1064	RM 40	100,0	50,0	50,0	450 SINGLE	7+3	28+20	95x150x160	275
M2304CO8	600 L	AR 1064	RM 40	100,0	50,0	100,0	500 DOUBLE	7+3	50+55	95x150x160	298

## AIRBLAST SPRAYER WITH FIXED CANNON

FRAME IN HOT-DIP GALVANIZED STEEL SECTIONS,  
POLYETHYLENE TANK WITH TOTAL EMPTYING AND FOLDING LID.

**Circuit washing tank.** Fresh water tank, external level, suction filter with valve, tank mixer, drain valve, remote controller.  
Hot galvanized fan casing, nozzle holder rods in stainless steel. Centrifugal impeller.  
2-speed gearbox with disengagement and CLUTCH, mechanical movements (inclination at 90°), single nozzles with membrane anti drip and ceramic nozzles of 1.5-1.2 mm.



## ATP Fixed Cannon

200 - 300 - 400 - 600 L

CODE	Tank capacity	Pump	Pressure Reg.	L/min	BAR	Absorbed power	Fan Ø	Nozzles	Spray Range A+B	Dimensions cm	Weight
<b>MOUNTED AIRBLAST SPRAYERS WITH FIXED CANNON</b>											
M2302CF9	200 L	AR 503	GR 30	55,0	40,0	25,0	400 SINGLE	4+6	25+15	80x120x160	200
M2303CF9	300 L	AR 503	GR 30	55,0	40,0	25,0	400 SINGLE	4+6	25+15	95x150x170	240
M2304CF6	400 L	AR 503	RM 40	55,0	40,0	25,0	400 SINGLE	4+6	25+15	95x150x170	245
M2304CF7	400 L	AR813	RM 40	80,0	50,0	30,0	400 SINGLE	4+6	25+15	95x150x170	254
M2304CF8	600 L	AR 1064	RM 40	100,0	50,0	50,0	450 SINGLE	7+3	30+18	95x150x170	264

### ACCESSORIES

LAVCIST	ROTATING NOZZLE FOR TANK WASHING (in combination with LAVCIRC)
KITLB	JUG WASHING KIT
M2002021	HYDRAULIC AGITATOR
DIM	MANUAL HYDRAULIC DISTRIBUTOR (WITH 2 LEVERS) with oleodinamic pipes (only for adjustable cannon head)
KITTUBI-C	KIT OF OLEODINAMIC PIPES (only for adjustable cannon head)
M2113010	ANTI DRIFT NOZZLES (specify the color)
M2093111	NOZZLES FOR THE LOW VOLUME DISTRIBUTION (specify the color)
EV2	REMOTE CONTROLLER TO ELECTRICALLY OPEN AND CLOSE FROM THE TRACTOR'S CAB
KITASP	SUCTION KIT WITH 5 M HOSE Ø 25 AND FILTER
KITSONARGEO	ON/OFF SENSOR FOR PLANT DETECTION
PIND	WATERPROOF DOCUMENT CONTAINER
KITRP.1	SWIVEL WHEEL SUPPORT (for 300-400 L) (adjustable on demand)
AN0206P	CARDAN SHAFT CAT.2 cm 60 (for 200 L)
AN0208P	CARDAN SHAFT CAT.2 cm 80 (for 300 L - 400 L)

### OPTIONAL

ODIS2EREG	REMOTE CONTROLLER WITH ELECTRIC PRESSURE REGULATION WITH ELECTRIC OPENING AND CLOSING AND PRESSURE GAUGE IN TRACTOR'S CAB
DIS2E	2-WAY ELECTRIC DISTRIBUTOR KIT+CONTROL PANEL
PISTIDR	HYDRAULIC PISTON FOR VERTICAL INCLINATION (only for fixed cannon)